

# ARMOPRIME AC

## Single Component Acrylic Based Primer/Sealer

### Description:

ARMOPRIME AC is a single component, water based, acrylic based, high quality primer. It is ideally used to waterproof the surface and improves adhesion of plaster, ceramic tiles, wall paper, etc. to the surface. The primer adheres to a variety of substrate and provides resistance to diluted acids and alkalis. It penetrates deeply in to the surface presenting features like dust roofing, integral waterproofing.

### Uses:

ARMOPRIME AC is used as a primer/sealer for:

- Anti-dust and hardening treatment for concrete flooring.
- Vapour barrier against capillary humidity.
- Primer for cement-based flooring systems.
- Can be used on AAC blocks and other porous surfaces to act as a sealer and as a bonding primer.
- Treatment of gypsum boards before plastering or before fixing tiles with cementitious adhesives.
- As protective treatment before the application of PLASTOMIX range of products.
- Sealer for concrete decorative flooring.

### Advantages:

- Excellent penetration to substrate.
- Closing pores to prevent dusting.
- Excellent adhesion to concrete, timber, granolithic screeds, masonry paving, mild steel etc.

### Instructions for Use:

#### Surface Preparation:

All surfaces should be sound, clean, dry and free from loose material, efflorescence, laitance, curing compounds, dirt, oil and grease. Ensure that concrete substrates are fully cured for at least 28 days.

### Mixing:

ARMOPRIME AC is a single component ready to use product. Shake the jerkin to ensure no settlement of materials.

### Application:

Apply ARMOPRIME AC with brush, roller or spray machine. Apply to substrate in rich amount to ensure proper penetration and coverage of the surface. The application rate varies between 3-4 m<sup>2</sup>/Lt, dependent on the porosity of substrate. For very porous substrate apply two coats of ARMOPRIME AC.

The product must penetrate in the support and must not remain in excess on surface. Consecutive works such as plastering, laying ceramic tiles or other coverings, should start immediately when the primer film surface is tacky and before it dries.

TECHNICAL PROPERTIES	
Appearance	Liquid
Color	Milky White
Density	1.02 ± 0.03 kg/lit
Recoat Interval	60 minutes
pH	8.5-10.5
Application Temp.	+5°C to +40°C
Noxiousity according to CEE 88/379	NIL
Flammability	No

\*Values indicated may vary depending on the environment and conditions of the material. Figures given are tested according to standard laboratory conditions.

### Coverage:

ARMOPRIME AC achieves coverage of approximately 3.5 square meters @ 100 micron dry film thickness for one ltr.

\*Coverage rate is an approximate value, and subject to actual site conditions.

### Packaging:

ARMOPRIME AC is available in 20 liter jerry can.

# ARMOPRIME AC

## Storage:

Store in original packing in dry conditions away from direct sunlight in a covered warehouse.

## Shelf Life:

ARMOPRIME AC can be utilized within 12 months of production date if stored in proper conditions in an unopened original packing.

## Cleaning:

Clean tools and equipment with water before material hardens. Hardened materials can only be removed mechanically

## Remarks:

- Do not apply where ambient temperatures are below 5°C.

## Health and Safety:

- Avoid contact with eyes and skin. Wear suitable protective clothing such as coveralls, goggles, dust mask and gloves. Use barrier cream. Ensure that there is adequate ventilation. Do not breathe vapour or spray mist.

## FIRST AID:

- Eyes: In the event of accidental splashes, flush with warm water and seek medical advice.
- Skin: Wash skin thoroughly with soap and water
- Inhalation: Remove to fresh air, keep patient rested
- Ingestion: Do not induce vomiting. Seek immediate medical attention.

For further safety information, please refer to ARMOPRIME AC Material Safety Data Sheet.

MATEX Rev.06-1123

*MATEX warrants that its products are free from material and manufacturing defects. Instructions on how to use the product should be strictly followed to ensure effectivity and safe use. MATEX shall not be liable either directly or indirectly for any damages to personal, equipment or products that may occur as a consequence of the failure of any products application because it has no direct or continuous control over where or how its products are applied. It is the user's responsibility to acquire always the updated version of datasheets.*

