

MEGASEAL CORD

Polyethylene Closed Cell Backing Rod

Description:

MEGASEAL CORD is a closed cell polyethylene foam supplied in circular cord lengths and available in different diameter sizes to fit all sizes of joints. It is characterized with minimal water absorption and highly weather proof.

MEGASEAL CORD is used at the base of joint openings to provide the proper support for sealants when applied in joints and can be applied for horizontal and vertical applications.

Uses:

MEGASEAL CORD is specifically used to provide a resilient filling and support base in expansion joints for the applied elastic sealant into the joint. It can be applied in all types of joints and in various areas of construction applications including:

- Expansion joints in walls and floors.
- Horizontal paving or traffic bearing joints.
- Joints between exterior facing panels.
- Isolation joints.
- Control joints in masonry walls.
- Pipes, ducts and vent openings.
- Precast roofs and prefabricated concrete panels.
- Around windows and door frames.

Advantages:

- Economical and easy to install.
- Provides proper shape factor and firm backing for sealant.
- Provides support for sealants in horizontal joints.
- Exceptionally flexible with superior resistance from deterioration.
- Act as bond breaker with minimum strain shape for joint sealants.
- Withstands adverse weather conditions

Instructions for Use:

Surface Preparation:

All the side surfaces of the joint must be dry, smooth, clean, free from dust, laitance or loose materials. To ensure proper cleaning. It is highly recommended to use compressed air or a wire brush in order to remove further dirt, oil stains and other inconsistencies.

Application:

The diameter of the MEGASEAL CORD is recommended to be approximately 20 to 25% larger than the width of the joint. It should be positioned so that the required minimum sealant depth can be obtained. The circular section of the backer rod provides a convex face giving a minimum strain shape for elastomeric sealants while reducing the stress at the bond interface.

TECHNICAL PROPERTIES	
Appearance	Compressible, closed cell, extruded polyethylene circular cord
Color	White or Grey
Thermal Conductivity	0.027 w/mk at 10°C
Density	25 kg/cm ³
Durability	Not subject to aging for 5 years
Tensile Strength Longitude Direction Lateral Direction	42.0 N/cm ² 34.0 N/cm ²
Elongation Longitude direction Lateral direction	80.0% 70.0%
Shore A hardness	25
Water absorption	NIL
UV resistance	5 years
Elasticity (%)	10
Temperature resistance	-20°C to +80°C
Resistance to Solvent	Good
Resistance to Deformation	Excellent
Dimensional Stability	Excellent

*Values indicated may vary depending on the environment and conditions of the material. Figures given are tested according to standard laboratory conditions.

MEGASEAL CORD

Storage:

Store away from direct sunlight in dry conditions.

Packaging:

MEGASEAL CORD is available in different diameters
50 LM long roll.

Available diameters: 10mm, 20 mm, 25mm, 30mm

Shelf Life:

5 years if stored in temperature controlled
warehouse.

Health and Safety:

There are no health hazards in connection with
MEGASEAL CORD in normal use.

MATEX Rev.01-0223

MATEX warrants that its products are free from material and manufacturing defects. Instructions on how to use the product should be strictly followed to ensure effectivity and safe use. MATEX shall not be liable either directly or indirectly for any damages to personal, equipment or products that may occur as a consequence of the failure of any products application because it has no direct or continuous control over where or how its products are applied. It is the user's responsibility to acquire always the updated version of datasheets.

