

# SEALEX SW

## Water Based Non-Staining Hydrophobic, Water Repellant Sealer

### Description:

SEALEX SW is a single component water based penetrative hydrophobic water repellent sealer, resins for concrete and masonry substrates. The chemistry of the silicate component is to react with moisture and water content of substrate to form a hydrophobic capillary blocking product. Therefore, it serves as a high quality, general purpose water repellent breathable sealer for impregnating and priming mineral and highly alkaline substrates.

SEALEX SW can be applied to concrete structure, cement plasters, bricks, light weight concrete, porous natural stones, and natural stone facades.

### Applications:

SEALEX SW used as a water repellent penetrative sealer at:

- Building facades, car parks, bridges.
- Natural stone facades for villas and buildings.
- Protection against the salt effects.
- Protection against weathering and rain.
- Primer for anti-carbonation system to prevent CO<sub>2</sub> and chloride ions ingress.
- Sealer and top coat for stained and stamped concrete after full curing.
- Maintenance of facades without altering colors and features.
- Primer for acrylic topping (anti-carbonation coatings or weather shield coatings) for porous surfaces.
- As a concrete sealer on a variety of surfaces such as EIFS System, colored plaster and exposed aggregate.

### Advantages:

- Cost effective sealer
- High penetration and water repelling efficiency
- Prevents carbon dioxide and chlorine ingress
- Resistant to UV, weathering and freeze/thaw cycles
- Integral application, durable
- Ease of application, applied manually or by a manual spray pump
- Allows concrete to breath, as water vapor permeability is unaffected

- Protects surface from discoloration
- No change in surface texture or appearance
- Clear, non-staining finish

### Instructions for Use:

#### Surface Preparation:

The surface of the concrete or plaster must be clean, solid, free from grease, and totally dry to guarantee maximum penetration. Oil or grease stains must be completely removed. All necessary repairs or crack filling should be completed before starts of application.

Surfaces with salty efflorescence must be cleaned mechanically or rinsed with water, allow surface to totally dries, before proceeding with the application

New concrete must be cured before applying SEALEX SW. All concrete curing compound must be mechanically removed, along with any foreign material.

#### Mixing:

Product is ready to use directly. It does not require thinning or other special preparations prior to application.

#### Application:

SEALEX SW must penetrate deep enough for greatest protection. To determine the ability to surface penetrate, apply on a smaller area first and observe if any excess liquid residue on surface that indicates improper penetration. In spite that one coat application will be sufficient, it is recommended to apply two coats to guarantee complete deep protection especially for porous surfaces.

SEALEX SW is applied directly to the substrate with a brush, roller, or spray machine which is highly recommended for wide areas. After testing the characteristic of the surface penetration, Apply a sufficient coat of SEALEX SW allow to become dry. Ensure proper coverage of first coat in a rate of 0.15 liter per square meter. The second coat should then be applied to the surface to provide the best possible protection. In case of porous surfaces Apply second

# SEALEX SW

coat within 3-6 hours from the application of the first coat.

The main indicator of full saturation is the tearing of the product while applying. However, excess material remaining on the surface after application should be spread out evenly or wiped off.

In case of applying SEALEX SW as a primer for anti-carbonation system, apply two rich coats of the product and then within 3 hours apply the subsequent coating of CARBOSHIELD-anti carbonation coating.

TECHNICAL PROPERTIES	
Description	Colorless Liquid
Density	1.0 kg/lit
Drying Time	3 hours
Chloride Permeability	NIL
Flash Point	>100°C
Solid Contents	27%
Chloride ingress	1%
Penetration through subs.	4-8 mm
VOC	30 g/l
Viscosity	9 cPs

\*Values indicated may vary depending on the environment and conditions of the material. Figures given are tested according to standard laboratory conditions.

## Coverage:

SEALEX SW coverage rate 6.0-8.0 square meters per liter per coat dependent highly on surface type and porosity. Testing the consumption rate by a sample application is highly recommended.

\*Coverage rate is an approximate value, and subject to actual site conditions.

## Packaging:

SEALEX SW is supplied in 20 liter jenkins and 200 liter drums.

## Storage Conditions:

Store in original packing in dry conditions away from direct sunlight.

## Cleaning:

Clean all tools with organic solvent prior to full drying of product.

## Shelf Life:

SEALEX SW can be utilized within 12 months of production date if stored in proper conditions in unopened original packing.

## Remarks:

- Good ventilation must be provided during application and curing.
- It should not be applied in outdoor applications during rainy weather or if rain is expected before complete curing can take place.
- Normally, the surface will become water resistant within 3–6 hours, but in cloudy, damp, cool or high humid conditions, curing may take longer.
- Spray application should be performed only with low pressure spray units to prevent excessive misting of the product.
- If spray application is used, a good painter's mask should be worn as a protective measure. Exposed food stuffs or other items which might be contaminated should be totally sealed or removed from the working area.
- This material reacts with atmospheric moisture. Prolonged contact with air should be avoided. Keep containers sealed when not in use.

# SEALEX SW

## Health and Safety:

Avoid contact with eyes and skin. Wear suitable protective clothing such as coveralls, goggles, dust mask and gloves. Use barrier cream. Ensure that there is adequate ventilation. Do not breathe vapour or spray mist.

### FIRST AID:

- Eyes: In the event of accidental splashes, flush with warm water and seek medical advice.
- Skin: Wash skin thoroughly with soap and water
- Inhalation: Remove to fresh air, keep patient rested
- Ingestion: Do not induce vomiting. Seek immediate medical attention.

For further safety information, please refer to SEALEX SW Material Safety Data Sheet.

MATEX Rev.03-0223

*MATEX warrants that its products are free from material and manufacturing defects. Instructions on how to use the product should be strictly followed to ensure effectivity and safe use. MATEX shall not be liable either directly or indirectly for any damages to personal, equipment or products that may occur as a consequence of the failure of any products application because it has no direct or continuous control over where or how its products are applied. It is the user's responsibility to acquire always the updated version of datasheets.*

